


## DIAL TEST INDICATORS

- Meet DIN2270 (except **2380-02**, **2381-02**, **2381-021**)
- Jeweled bearing
- Carbide contact point
- Two measuring directions
- Anti magnetic body
- Supplied with two clamps: diameter  $\varnothing 4$ mm and  $\varnothing 8$ mm
- Optional accessory: styli (page 170)



2380-08

(mm)

Code	Range	Graduation	Accuracy	Hysteresis	Dial reading	A	L
<b>2380-08*</b>	0.8mm	0.01mm	13 $\mu$ m	3 $\mu$ m	0-40-0	$\varnothing 30$	13.5
<b>2381-08*</b>	0.8mm	0.01mm	13 $\mu$ m	3 $\mu$ m	0-40-0	$\varnothing 37$	13.5
<b>2380-02*</b>	0.2mm	0.002mm	6 $\mu$ m	2 $\mu$ m	0-100-0	$\varnothing 30$	12.5
<b>2381-02*</b>	0.2mm	0.002mm	6 $\mu$ m	2 $\mu$ m	0-100-0	$\varnothing 37$	12.5
<b>2381-021*</b>	0.2mm	0.001mm	6 $\mu$ m	2 $\mu$ m	0-100-0	$\varnothing 37$	12.5

\* Supplied with manufacturer inspection certificate traceable to NIST USA

