



Model No.	Assembly (mm)				BR block (mm)							BR rail (mm)			
	H	W	W2	E	L	BxJ	MQx	L1	Oil hole	T1	(N)	W1	H1	F	dxDxh
BRH15A	24	47	16	4.6	66	38x30	M5x8	40	Φ 3	4.3	5	15	14	60	4.5x7.5x5.3
BRH20A	30	63	21.5	5	77.8	53x40	M6x9	48.8	M6x1	7	15.6	20	18	60	6x9.5x8.5
BRH20AL					92.4			63.4							
BRH25A	36	70	23.5	7	88	57x45	M8x12	57	M6x1	7.8	15.6	23	22	60	7x11x9
BRH25AL					110.1			79.1							
BRH30A	42	90	31	9	109	72x52	M10x12	72	M6x1	7	15.6	28	26	80	9x14x12
BRH30AL					131.3			94.3							
BRH35A	48	100	33	9.5	109	82x62	M10x13	80	M6x1	8	15.6	34	29	80	9x14x12
BRH35AL					134.8			105.8							
BRH45A	60	120	37.5	14	133	100x80	M12x15	95	M8x1	8.5	16	45	38	105	14x20x17
BRH45AL					167.8			129.8							

Model No.	Ref.Data (mm)		Basic Load Rating (Kgf)		Static Moment (Kgf*m)			Weight	
	Lmax	G	(C)	(CO)	Mx	My	Mz	Block(Kg)	Rail(Kg/m)
BRH15A	4000	20	850	1350	10.1	6.8	6.8	0.21	1.4
BRH20A	4000	20	1400	2400	24	14.6	14.6	0.4	2.6
BRH20AL			1650	3000	30	23.8	23.8		
BRH25A	4000	20	1950	3200	36.8	22.8	22.8	0.57	3.6
BRH25AL			2600	4600	52.9	45.5	45.5	0.72	
BRH30A	4000	20	2850	4800	67.2	43.2	43.2	1.1	5.2
BRH30AL			3600	6400	89.6	75.4	75.4	1.4	
BRH35A	4000	20	3850	6200	105.4	62	62	1.6	7.2
BRH35AL			4800	8300	141.1	109.8	109.8	2	
BRH45A	4000	22.5	6500	10500	236.3	137.8	137.8	2.7	12.3
BRH45AL			7700	13000	292.5	210.9	210.9	3.6	